


Miniature 08 Series Modular Air Preparation System


Regulator R08



R08-C2-F0G0



Relieving



Non-Relieving

Features

- Balanced Valve Design
- 2 Gauge Ports
- Serviceability and Ease of Maintenance
- Unique Flush-mounted Pressure Gauge
- Light Weight
- Modern Design and Appearance

Options:

R08	-	C	2	-	F	0	0	0
------------	---	----------	----------	---	----------	----------	----------	----------

Thread type	
NPT	0
BSPP	C

Pipe size	
1/8	1
1/4	2

Diaphragm/Spring Options	
Nitrile - 2 bar - Relieving	C
Nitrile - 4 bar - Relieving	D
Nitrile - 8 bar - Relieving	F
Fluorocarbon - 2 bar - Relieving	J
Fluorocarbon - 4 bar - Relieving	K
Fluorocarbon - 8 bar - Relieving	L
Nitrile - 2 bar - Non Relieving	P
Nitrile - 4 bar - Non Relieving	W
Nitrile - 8 bar - Non Relieving	R
Fluorocarbon - 2 bar - Non Relieving	V
Fluorocarbon - 4 bar - Non Relieving	X
Fluorocarbon - 8 bar - Non Relieving	Y

Options	
None	0

Option 1	
None	0
Gauge, Pressure, Flush mount	G
Nut, Panel mount, Metal	P
Regulator reverse flow capability	R

Option 2	
None	0
Gauge, Pressure, Flush mount	G
Nut, Panel mount, Metal	P
Regulator reverse flow capability	R

Note: NPT ports and other options available on request.

Ordering Information - Standard Options

Model Type	Port Size	With Gauge	With Gauge	With Gauge	Without Gauge	Without Gauge	Without Gauge
		0 to 8,6 bar	0 to 2,1 bar	0 to 4,1 bar	0 to 8,6 bar	0 to 2,1 bar	0 to 4,1 bar
Relieving	1/8	R08-C1-F0G0	R08-C1-C0G0	R08-C1-D0G0	R08-C1-F000	R08-C1-C000	R08-C1-D000
	1/4	R08-C2-F0G0	R08-C2-C0G0	R08-C2-D0G0	R08-C2-F000	R08-C2-C000	R08-C2-D000
Non-relieving	1/8	R08-C1-R0G0	R08-C1-P0G0	R08-C1-W0G0	R08-C1-R000	R08-C1-P000	R08-C1-W000
	1/4	R08-C2-R0G0	R08-C2-P0G0	R08-C2-W0G0	R08-C2-R000	R08-C2-P000	R08-C2-W000

Options - To order an option supplied with the unit model, add the appropriate coded suffix letter in the designated position of the model number. For additional information on accessories and repair kits refer to the Table of Contents.