

## Dilos

### Dilos 4 - Loadbreak disconnectors for wall mounting

Transparent	Description	In (A)	Cat. No.	Ref. No.	Pack
	3-pole	400	D/061344-201	<b>730474</b>	1
	With padlockable rotary handle	500	D/061345-201	<b>730476</b>	1
		630	D/061346-201	<b>730478</b>	1
		3-pole + neutral	400	D/061444-201	<b>730502</b>
	With padlockable rotary handle	500	D/061445-201	<b>730504</b>	1
		630	D/061446-201	<b>730506</b>	1
		3-pole + fixed neutral	400	D/061544-201	<b>730530</b>
	With padlockable rotary handle	500	D/061545-201	<b>730532</b>	1
		630	D/061546-201	<b>730534</b>	1

### Accessories Dilos 4

	Description		Cat. No.	Ref. No.	Pack
	<b>Direct handles</b>				
	Low black		D/061950-252	<b>731540</b>	1
	With keylock possibility (keylock not included)		D/061950-251	<b>730653</b>	1
	<b>Handles for cover or hinged door</b>				
	IP54 - Defeat - Padlockable				
	With extension shaft 300 mm (14/14)		D/062940-241	<b>730667</b>	1
	Grey		D/062940-281	<b>730855</b>	1
	Set for discon. with N on the right: grey				
	<b>Handles for inner door</b>				
	IP65 - Padlockable				
	Black, reduced height 55 mm - With extension shaft 300 mm		D/062947-202	<b>731352</b>	1
	<b>Keylock</b>				
	Plug-in for handles		D/769080-000	<b>769080</b>	1
	<b>Changeover system (I-O-II)</b>				
	With extension shaft 300 mm, padlockable handle, gasket, flange and template				
	With handle IP54 - defeat		D/062940-265	<b>730669</b>	1
	As above but with handle 55 mm height - for inner door		D/062947-265	<b>731457</b>	1
	With black handle IP65				
	<b>Standard auxiliary contacts</b>				
	To be added on the right side				
	1P CO		D/061901-001	<b>730252</b>	1
	2P CO		D/061901-002	<b>730253</b>	1
	<b>Max. current rating for AC 15 and DC 13</b>				
	AC 3A at 380V				
	5A at 220V				
	DC 0.5A at 220V				
	0.7A at 110V				
	1A at 60V				
	2A at 48V				
	4A at 24V				