


HSK-EMC cable glands

HSK-M-EMV

Metr., Metr.-elongated




Material	Nickel plated brass
Clamping insert	Polyamide
Seal	Buna-N
O-Ring	Buna-N
Protection	IP 68 – 10 bar / IP 69K (NEMA 6 – 150 PSIG) within the specified clamping range
Operating Temperature	-40 °C – 100 °C (-40 °F – 212 °F)



Advice:
 - Other sealing material e.g. Silicone upon request
 - Stainless steel on request

See our homepage www.hummel.com
 for assembling advices for maximum
 cable diameters



AG	\varnothing mm	GL mm	H mm	\varnothing mm	Number	GL mm	Number long
M 12 x 1,5	3 – 6,5	6,5	19	14	1.691.1200.50	10	1.691.1200.30
M 12 x 1,5	2 – 5	6,5	19	14	1.691.1200.51	10	1.691.1200.31
M 16 x 1,5	5 – 10	6	22	20	1.691.1600.50	10	1.691.1600.30
M 16 x 1,5	3 – 7	6	22	20	1.691.1600.51	10	1.691.1600.31
M 20 x 1,5	10 – 14	6	24	24	1.691.2000.50	10	1.691.2000.30
M 20 x 1,5	7 – 12	6	24	24	1.691.2000.51	10	1.691.2000.31
M 25 x 1,5	13 – 18	7	26	30	1.691.2500.50	12	1.691.2500.30
M 25 x 1,5	9 – 16	7	26	30	1.691.2500.51	12	1.691.2500.31
M 32 x 1,5	18 – 25	8	31	40	1.691.3200.50	12	1.691.3200.30
M 32 x 1,5	13 – 20	8	31	40	1.691.3200.51	12	1.691.3200.31
M 40 x 1,5	22 – 32	8	37	50	1.691.4000.50	15	1.691.4000.30
M 40 x 1,5	20 – 26	8	37	50	1.691.4000.51	15	1.691.4000.31
M 50 x 1,5	32 – 38	9	37	57	1.691.5000.50	15	1.691.5000.30
M 50 x 1,5	25 – 31	9	37	57	1.691.5000.51	15	1.691.5000.31
M 63 x 1,5	37 – 44	10	38	64 / 68	1.691.6300.50	15	1.691.6300.30
M 63 x 1,5	29 – 35	10	38	64 / 68	1.691.6300.51	15	1.691.6300.31



➔ Accessories see page 71