

| | | | Part no. | Pk. | Change-over relays (mini-relays) |
|--|--|--|-----------------|-----|---|
| | | | 4RD 003 520-131 | 1 | With 6.3 mm blade terminal contacts. Max. load (at +80 °C) 40/20A at 12V, 30/15A at 24V. |
| | | | 4RD 003 520-137 | 330 | |
| | | | 4RD 003 520-071 | 1 | 24V |
| | | | 4RD 003 520-077 | 330 | |
| | | | 4RD 003 520-081 | 1 | With bracket, 12V |
| | | | 4RD 003 520-088 | 270 | |
| | | | 4RD 003 520-091 | 1 | 24V |
| | | | 4RD 003 520-097 | 270 | |
| | | | 4RD 007 794-021 | 1 | With resistor. Inductive interference-voltage spikes from the coil limited by resistor in parallel to < 90V. With 6.3 mm blade terminal contacts. Max. load (at +80 °C) 40/20A at 12V and 24V. |
| | | | 4RD 007 794-027 | 225 | |
| | | | 4RD 007 903-001 | 1 | 24V |
| | | | 4RD 007 903-007 | 192 | |
| | | | 4RD 007 794-077 | 225 | as -021, but base plate without ventilation hole |
| | | | | | |
| | | | 4RD 007 903-011 | 1 | 24V |
| | | | 4RD 007 903-017 | 240 | |
| | | | 4RD 003 520-221 | 1 | Max. load (at +80 °C) 30A/15A at 24V. Change-over relay, 5-pin, without bracket, 24V |
| | | | 4RD 003 520-227 | 330 | |
| | | | 4RD 007 794-041 | 1 | Change-over relay, 5-pin, 12V |
| | | | 4RD 007 794-047 | 192 | |
| | | | 4RD 003 520-251 | 1 | 12V |
| | | | 4RD 003 520-257 | 330 | |
| | | | 4RD 007 903-021 | 1 | 24V |
| | | | 4RD 007 903-027 | 192 | |
| | | | 4RD 003 520-151 | 1 | 24V |
| | | | 4RD 003 520-157 | 100 | |
| | | | 4RD 003 520-667 | 1 | With bracket and diode, 24V |