

712/714 Temperature Calibrators

FLUKE®



Fluke 714



Fluke 712

The clear choice

The Fluke 710 Series Process Calibrators offer clear new choices in single-function calibrators. Whatever you want to measure - temperature, pressure or basic electrical parameters - you'll find one of these easy-to-carry handheld tools gives you exactly the functions you need. They combine the rugged, ready-for-action package of the proven Fluke 80 Series DMMs with the easy-to-use pushbutton operation of the multifunction Fluke 740 Series Documenting Process Calibrators. These calibrators are EMI tolerant, dust and splash resistant, and have a removable battery door for quick battery changes.

712 RTD Calibrator

- Measure temperature from RTD output
- Simulate RTD output
- Rosemount pulsed RTD transmitter compatible
- Operates with seven types of RTDs
- Measure additional RTDs using Ohms measurement function
- Simulate additional RTDs using Ohms source function
- °F or °C selectable
- Four shrouded banana jacks

714 Thermocouple Calibrator

- Measure temperature from TC output
- Simulate TC output
- Operable with nine types of thermocouples
- Calibrate linear TC transmitter with mV source function
- Selectable °F or °C
- Thermocouple mini-jack termination
- Available as accessories; Fluke 700 TC1 and TC2 Thermocouple Mini-plug Kits

Specifications

| Model | Function | Range | Resolution | Accuracy | Notes |
|-----------|--------------------------------|---|------------------------------|------------------------|--|
| Fluke 712 | Measure/simulate RTD | -200 to 800°C (Pt 100) | 0.1°C, 0.1°F | 0.33°C, 0.6°F (Pt 100) | Pt: 100 200 500 1000 (385); Pt 100 (3926); Pt 100 (3916) JIS; Ni 120 (672) |
| | Measure/simulate Resistance | 15 Ω to 3200 Ω | 0.1 Ω | 0.1 Ω to 1 Ω | |
| Fluke 714 | Measure/ simulate Thermocouple | -200 to 1800°C, depending on type (K, -200 to 1370°C) | 0.1°C or °F (1°C or °F; BRS) | 0.3°C to 10 μV | 9 TC types: J K T E R S B per NIST 175 and ITS-90, L U per DIN 43710 and IPTS-68 |
| | Measure/ simulate mV | -10 to 75 mV | 0.01 mV | 0.025% + 1 count | |



Included Accessories

Yellow Holster (H80M excl. TPAK), TL75 Test Leads and AC72 Alligator Clips (excluding model 714), single 9V alkaline battery and Instruction Sheet (14 languages)

Ordering Information

Fluke 712 RTD Calibrator
Fluke 714 Thermocouple Calibrator

General specifications for Fluke 712/714/715/717/718/718Ex

Maximum voltage: 30 V
Non-operating temperature: -40°C to 60°C
Operating temperature: -10°C to 55°C
Relative humidity: 95% (10°C to 30°C); 75% (30°C to 40°C); 45% (40°C to 50°C); 35% (50°C to 55°C)
Operating altitude: 3,000m max
Shock: 1m drop test
Vibration: Random, 2g, 5-500 Hz
Safety: CSA C22.2 No. 1010.1:1992

EMC: EN50082-1:1992 and EN55022: 1994 Class B
712/714:
Size (HxWxD): 201mm x 98mm x 52mm
Weight: 0.6kg
Battery: 9V alkaline
Battery Life: 4 to 20 hours, typical, depending on functions used
Three Year Warranty

Recommended Accessories



C25



C550



TL75 (712)



TL220 (714)



80PK-24 (714)